Model identifier(s): Scar	n 66 - 1, 2, 3	, 4						
Indirect heating functionality				No				
Direct heat output(kW)				5				
Indirect heat output(kW)				N.A				
Fuel				Preferred fuel (only one)	Model	identifier(s)	)	
Wood logs with moisture content ← 25%				Yes	No	No		
Compressed wood with moisture content < 12%				No	No	No		
Other woody biomass				No	No	No		
Anthracite and dry steam coal				No	No			
Hard coke				No	No			
Low temperature coke				No	No			
Bituminous coal				No	No	No		
Lignite briquettes				No	No			
Peat briquettes				No	No	No		
Blended fossil fuel briquettes				No	No	-		
Other fossil fuel				No	No			
Blended biomass and fossil fuel briquettes				No	No			
Other blend of biomass and solid fuel				No	No	No		
Characteristics when operating with the preferred fuel								
Seasonal space heating energy efficiency η <sub>s</sub> [%]				69				
Energy Efficiency Class				A+				
Energy Efficiency Index (EEI)			104,1					
ltem	Symbol	Value	Unit	ltem	Symbol	Value	Unit	
Heat output	I			Use efficiency (NCV as re	eceived)			
Nominal heat output	P <sub>nom</sub>	5	kW	Useful efficiency at nominal heat output	$\eta_{\text{th, nom}}$	78	%	
Minimum heat output (indicative)	$P_{min}$	N.A.	kW	Useful efficiency at minimum heat output (indicative)	$\eta_{_{\text{th, min}}}$	N.A.	%	
Auxiliary electricity consumption				Type of heat output/roo	m temperat	ure control	select one)	
At nominal heat output	el <sub>max</sub>	X,XXX	kW	single stage heat output, no room temperature control		[yes/no]		
At minimum heat output	el <sub>min</sub>	x,xxx	kW	two or more manual stages, no room temperature control		[yes/no]	Yes	
In standby mode	el <sub>sB</sub>	x,xxx	kW	with mechanic thermostat room temperature control		[yes/no]		
				with electronic room temperature control		[yes/no]		
				with electronic room temperature control plus day timer		[yes/no]		
				with electronic room temperature control plus week timer		[yes/no]		
				Other control options (multiple		tions possible	)	
	room temperature control, w		ol, with	[yes/no]				
				room temperature contr open window detection	[yes/no]			
with distance control option				tion	[yes/no]			
Permanent pilot flame p	ement							
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	N.A.	kW					
Contact details  Name and address of the supplier:  Brian Ørum, R&D Markager, Scan A/S, Denmark								